

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶:

A61F 9/007, A61B 17/32 // 19/00

(11) International Publication Number:

NL, PT, SE).

WO 99/15120

(43) International Publication Date:

1 April 1999 (01.04.99)

(21) International Application Number:

PCT/US98/14767

A1

(22) International Filing Date:

16 July 1998 (16.07.98)

(30) Priority Data:

08/935,797

23 September 1997 (23.09.97) US

Published

With international search report.

(81) Designated States: AU, BR, CA, JP, European patent (AT, BE,


CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,

(71) Applicant: ALCON LABORATORIES, INC. [US/US]; 6201 South Freeway, Fort Worth, TX 76134-2099 (US).

(72) Inventor: CAPETAN, Thomas, G.; 3817 Mockingbird Lane, Fort Worth, TX 76109 (US).

(74) Agents: SCHIRA, Jeffrey, S. et al.; Alcon Laboratories, Inc., R & D Legal Dept., Q-148, 6201 South Freeway, Fort Worth, TX 76134-2099 (US).

(54) Title: SURGICAL HANDPIECE



(57) Abstract

A surgical handpiece having a central operative core which is removably received in an outer shell. The operative core and outer shell is easier to manufacture and assemble, thereby decreasing cost and increasing reliability.

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
ΑZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	T.J	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	ÜA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		•
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		•
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

5

10

15

20

25

30

SURGICAL HANDPIECE

This invention relates to surgical handpieces and more particularly to an ophthalmic phacoemulsification handpiece.

Background of the Invention

A typical ultrasonic surgical device suitable for ophthalmic procedures consists of an ultrasonically driven handpiece, an attached hollow cutting tip, an irrigating sleeve and an electronic control console. The handpiece assembly is attached to the control console by an electric cable and flexible tubings. Through the electric cable, the console varies the power level transmitted by the handpiece to the attached cutting tip and the flexible tubings supply irrigation fluid to and draw aspiration fluid from the eye through the handpiece assembly.

The operative part of the handpiece is a centrally located, hollow resonating bar or hom directly attached to a set of piezoelectric crystals. The crystals supply the required ultrasonic vibration needed to drive both the hom and the attached cutting tip during phacoemulsification and are controlled by the console. The crystal/hom assembly is suspended within the hollow body or shell of the handpiece at its nodal points by relatively inflexible mountings. The handpiece body terminates in a reduced diameter portion or nosecone at the body's distal end. The nosecone is externally threaded to accept the irrigation sleeve. Likewise, the hom bore is internally threaded at its distal end to receive the external threads of the cutting tip. The irrigation sleeve also has an internally threaded bore that is screwed onto the external threads of the nosecone. The cutting tip is adjusted so that the tip projects only a predetermined amount past the open end of the irrigating sleeve. Ultrasonic handpieces and cutting tips are more fully described in U.S. Pat. Nos. 3,589,363; 4,223,676; 4,246,902; 4,493,694; 4,515,583; 4,589,415; 4,609,368; 4,869,715; 4,922,902 and 5,178,605 the entire contents of which are incorporated herein by reference.

When used to perform phacoemulsification, the ends of the cutting tip and irrigating sleeve are inserted into a small incision of predetermined width in the cornea, sclera, or other location in the eye tissue in order to gain access to the anterior chamber of the eye. The cutting tip is ultrasonically vibrated along its longitudinal axis within the

5

10

15

20

25

30

the selected tissue in situ. The hollow bore of the cutting tip communicates with the bore in the horn and the piezoelectric crystals that in turn communicates with the aspiration line from the handpiece to the console. A reduced pressure or vacuum source in the console draws or aspirates the emulsified tissue from the eye through the open end of the cutting tip, the bore of the cutting tip, the horn bore, and the aspiration line and into a collection device. The aspiration of emulsified tissue is aided by a saline flushing solution or irrigant that is injected into the surgical site through the small annular gap between the inside surface of the irrigating sleeve and the outside surface of the cutting tip. This small annular gap separates the vibrating, hot tip from eye tissue and the flow of fluid within the gap cools the tip. In some cases, the gap and the fluid flow are insufficient to prevent the burning of tissue.

Prior to the present invention, phacoemulsification handpieces were relatively expensive due to the cost of the materials and the precise machining required in manufacturing the handpieces. As a result, phacoemulsification handpiece are not disposed of at the end of surgery, but are reused a number of times. Handpieces that are reused must be sterilized, usually by steam autoclaving. Steam autoclaving is extremely injurious to the seals, piezoelectric crystals and other electrical components of the handpiece. As a result, prior art phacoemulsification handpieces can be unreliable and must be rebuilt frequently. Additionally, prior art handpieces require numerous connections to a surgical console, making the handpieces more difficult and time consuming to set up.

Accordingly, a need continues to exist for a simple, reliable and safer surgical handpiece.

Brief Summary of the Invention

The present invention improves upon prior art handpieces by providing a handpiece having a central core which is removably received in an outer shell. The central core may be an ultrasonic element, a laser element or any other desired operative core and the core and/or the outer shell may be intended as a single use disposable or reusable element. A separate core and outer shell is easier to manufacture and the core does not have to be

5

10

15

20

25

30

steam autoclaved. In addition, all the required connections for the handpiece can be preassembled on the handpiece and for easy connection to the surgical console, thereby reducing set up time.

Accordingly one objective of the present invention is to provide an inexpensive surgical handpiece.

Another objective of the present invention is to provide a surgical handpiece having increased reliability.

Still another objective of the present invention is to provide a phacoemulsification handpiece having a solid resonating core and tip.

Other objects, features and advantages of the present invention will become apparent with reference to the drawings, and the following description of the drawings and claims.

Brief Description of the Drawings

- FIG. 1 is an expanded prospective view of the first embodiment of the surgical handpiece of the present invention.
- FIG. 2 is a cross-sectional view of the first embodiment of the surgical handpiece of the present invention.
 - FIG. 3 is a cross-sectional view of the second embodiment of the surgical handpiece of the present invention.
- FIG. 4 is an expanded prospective view of the second embodiment of the surgical handpiece of the present invention.

Detailed Description of the Invention

As best seen in FIG. 1, handpiece 10 of the present invention preferably may be a phacoemulsification handpiece which will generally includes resonating core 12 and outer shell 14. Core 12 generally includes piezoelectric crystal portion 16, horn 18 and solid tip 20. Horn 18 and tip 20 preferably are machined as a single piece from any suitable material, for example, titanium, but the tip can be removable using a screw connector. Crystals 16 are attached to horn 18 at one end 22 by any suitable means, for example,

WO 99/15120 PCT/US98/14767

epoxy glue and contain electrical connector and seal 24 at the opposite end that allows handpiece 10 to be connected to a suitable power and control source (not shown) through cable 26. Crystals 16 are caused to vibrate in a manner well-known in the art.

Handpiece 10 may also be used as a laser handpiece, an irrigation/aspiration handpiece, a liquefaction handpiece or any other desired handpiece by appropriate substitution of core 12.

5

10

15

20

Shell 14 contains aspiration port 28, irrigation port 30, integral aspiration sleeve 32 and integral irrigation sleeve 34. As best seen in FIG. 2, aspiration port 28 communicates with aspiration sleeve 32 through internal aspiration line 36, and irrigation port 30 communicates with irrigation sleeve 34 through internal irrigation line 38. The use of dual sleeves 32 and 34 provides further isolation of tip 20 from tissue. Shell 14 may be made of any suitable material such as stainless steel, titanium or plastic. Suitable external tubings 29 and 31 can be preassembled to aspiration port 28 and irrigation port 30 and made to conveniently connect to the surgical console (not shown), for example, by preconnecting tubings 29 and 31 to the surgical cassette (not shown) that may be used with the console.

As best seen in FIGS. 2 and 3, when core 12 is inserted into shell 14, tip 20 is coaxially sealed fluid tight within aspiration sleeve 32 by seal 40. Core 12 may be sealed within shell 14 by a friction connector/seal 24, as shown in FIGS. 1 and 2, or screw connector/seal 124, as shown in FIGS. 3 and 4.

While certain embodiments of the present invention have been described above, these descriptions are given for purposes of illustration and explanation. Variations, changes, modifications and departures from the systems and methods disclosed above may be adopted without departure from the scope or spirit of the present invention.


I claim:


- 1. A surgical handpiece, comprising:
- a) a core having a piezoelectric crystal portion and a horn portion, the horn
- portion having an integral solid cutting tip and attached to the crystal portion;
- b) a hollow outer shell having internal aspiration and irrigation lines that
- communicate with integral aspiration and irrigation sleeves, respectively, the shell
- adapted to receive the core;
- c) a seal for sealing the solid cutting tip within the irrigation sleeve; and
- d) a connector for sealing the core within the shell.
- The handpiece of claim 1 wherein the connector is a friction seal.
 - 3. The handpiece of claim 1 wherein the connector is a screw seal.
- 1 4. The handpiece of claim 1 wherein external tubings are preassembled to 2 ports on the shell.
- 5. A surgical handpiece, comprising:
- a) an operative core;


1 %

4

- b) a hollow outer shell having internal aspiration and irrigation lines that
- 4 communicate with integral aspiration and irrigation sleeves, respectively, the shell
- s adapted to receive the core; and
- 6 c) a connector for sealing the core within the shell.
- 1 6. The handpiece of claim 5 wherein the connector is a friction seal.
- 7. The handpiece of claim 5 wherein the connector is a screw seal.
- 1 8. The handpiece of claim 5 wherein external tubings are preassembled to 2 ports on the shell.







INTERNATIONAL SEARCH REPORT

Inte tional application No.

PCT/US 98/14767

	1 - 1,7 55	30/14/0/				
A. CLASSIFICATION OF SUBJECT MATTER						
IPC6: A61F 9/007, A61B 17/32 // A 61 B 19/00 According to International Patent Classification (IPC) or to both national classification and IPC						
B. FIELDS SEARCHED						
Minimum documentation searched (classification system followed by	classification symbols)					
IPC6: A61B, A61F						
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched						
Electronic data base consulted during the international search (name	of data base and, where practicable,	search terms used)				
EPODOC, WPI MEDLINE						
C. DOCUMENTS CONSIDERED TO BE RELEVANT						
Category* Citation of document, with indication, where app	ropriate, of the relevant passage	Relevant to claim No.				
Y US 3805787 A (A. BANKO), 23 Apri column 5, line 8 - line 35,		1-8				
Y US 3994297 A (J.D. KOPF), 30 Nove	ember 1976	1-8				
(30.11.76), column 2, line 5 1-2						
A US 4316465 A (R.S. DOTSON, JR.), (23.02.82), figures 1-3	23 February 1982	1-8				
A US 5344395 A (M.J. WHALEN ET AL.) (06.09.94), figures 1-4), 6 Sept 1994	1-8				
X Further documents are listed in the continuation of Box C. X See patent family annex.						
* Special categories of cited documents: To later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention.						
"E" criter document but published on or after the international filing date "I." document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other.						
special reason (as specified) "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such committee the observation of the international filing date but fater than						
the priority date claimed "&" document member of the same patent family						
Date of the actual completion of the international search Date of mailing of the international search report						
18 December 1998	12.01.99					
Name and mailing address of the ISA Authorized officer						
Furopean Patent Office, P.B. 5818 Patentlaan 2 N12280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31-651 epo nl.						

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 98/14767

		101/03 30/	14707
C (Continu	nation). DOCUMENTS CONSIDERED TO BE RELEVANT		
ategory*	Citation of document, with indication, where appropriate, of the relev	ant passages	Relevant to claim No.
A	WO 8903202 A1 (SCHNEIDER, RICHARD, T.), 20 April 1989 (20.04.89), figure 2		1-8
A	 WO 9218075 A1 (ALLERGAN, INC.), 29 October 199 (29.10.92), figures 8-9	92	1-8
	^_		
	· ·		
	·		
			·
		•	

INTERNATIONAL SEARCH REPORT


Information on patent family members

01/12/98


International application No. PCT/US 98/14767


Patent document cited in search report		Patent family member(s)	Publication date
3805787	05787 A 23/04/74	NONE	
3994297	94297 A 30/11/76	NONE	
4316465	16465 A 23/02/82	US 4274411 A	23/06/81
5 5344395	44395 A 06/09/94	US 5085662 A US 5423838 A CA 2083525 A EP 0554616 A JP 5261114 A	04/02/92 13/06/95 25/07/93 11/08/93 12/10/93
8903202	03202 A1 20/04/89	NONE	
9218075	18075 A1 29/10/92	AT 153525 T DE 69220056 D,T EP 0585322 A,B JP 6507094 T US 5242449 A US 5364405 A AU 3697993 A CA 2092746 A	15/06/97 30/10/97 09/03/94 11/08/94 07/09/93 15/11/94 21/10/93 17/10/93

THIS PAGE BLANK (USPTO)



•





Michigan Commence

THIS PAGE BLANK (USPTO)

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:				
BLACK BORDERS				
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES				
☐ FADED TEXT OR DRAWING				
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING				
☐ SKEWED/SLANTED IMAGES				
COLOR OR BLACK AND WHITE PHOTOGRAPHS				
☐ GRAY SCALE DOCUMENTS .				
☐ LINES OR MARKS ON ORIGINAL DOCUMENT				
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY				
П отнер.				

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)